

# Graffiti Protect

## Product description

Graffiti Protect is an integral part of the **ecgo-system®** and is specially developed to protect brick, concrete and stone surfaces from long term damage due to graffiti attack. Its unique wax based formulation protects the underlying surface from the permeation of paint particles, keeping the surface clean and free from unwanted graffiti.

The innovative structure of **ecgo®** Graffiti Protect means the protective layer absorbs less contamination than conventional wax-based products and the treated surface also becomes water repellent yet vapour permeable, ensuring full breathability of the structure. In addition to its repellent and permeable properties, this product is fully UV and weather resistant and will last for up to 2 years (under normal weathering conditions).

**ecgo®** Graffiti Protect is fully transparent and acts as an invisible protective layer for both painted and unpainted surfaces such as concrete, rendered plaster, stonework and other mineral surfaces. Due to its matt effect, this product is not suitable for high gloss surfaces such as glass or metal.

This product is ready to use as a liquid and can be easily applied using a paint brush, roller or spray applicator. Shake contents before use. For most surfaces we recommend 2 coats.

## How to use

### STEP 1:

Ensure surface is clean and dry. Use **ecgo®** Multi Surface Cleaner to remove any dirt and grime residues, or if area has been attacked by graffiti, then use the **ecgo®** Graffiti Remover before applying the protective coating.

### STEP 2:

Apply product evenly on to the surface using a paint brush, roller or a spray applicator.

### STEP 3:

Allow primary layer to cure. Surface is ready for application of second coat after approximately 30 mins.

### STEP 4:

Apply second coat, ensuring full coverage. Protective layer is fully functional after 1 hr. Some highly porous and rough surfaces may require a third coating to ensure full protection. If so, follow steps 3 and 4 again.

Coverage: Depending on the surface and the degree of pollution use 0.1 – 0.4 l/m<sup>2</sup>.

## Mineral

Designed to work on mineral surfaces. Always read the label.

## Notes

**ecgo®** Graffiti Protect should be protected from temperatures below 5°C whilst in storage. Once applied and set, product is fully resistant to cold temperatures.

Please follow the instructions for proper use, storage and disposal. Product should be stored in the original containers only.

Data provided is subject to change.