Product identifier Name of product Classic Lemon Fresh 270ml Art-Nr W202 Relevant identified uses of the substance or mixture and uses advised against Details of the supplier of the safety data sheet Distributor P+L Systems Ltd. Ten St James Business Park, Grimbald Crag Court, UK-HG5 8QB Knaresborough Phone 0044 (0) 800 988 5359, Fax 0044 (0) 1 423 863 497 E-Mail info@pandlsystems.com Internet www.pandlsystems.com Advice Phone 0044 (0) 1 412 861 226 **Emergency telephone number** Manufacturer Colep Bad Schmiedeberg GmbH Kemberger Str.3, D-06905 Bad Schmiedeberg Phone +49 (34925) 76-0, Fax +49 (34925) 76-299 Internet www.colep.com Advice Application Phone +49 (34925) 76-0 Fax +49 (34925) 76-299 E-mail (competent person): Steffen.Bruehmann@colep.com **Emergency telephone number** Herr Brühmann Emergency advice

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Phone +49 (34925) 76-0 This number is only available at office times.

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to 67/548/EEC or 1999/45/EC

F+; R12	
R43	
R52	
R53	
R-phrases	
12	Extremely flammable.
43	May cause sensitisation by skin contact.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Label elements

Labelling according to 67/548/EEC or 1999/45/EC

F+ Extremely flammable





R-phrases

12	Extremely flammable.
43	May cause sensitisation by skin contact.
52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic
	environment.

S-phrases

2	Keep out of the reach of children.
23	Do not breathe spray.
24	Avoid contact with skin.
37	Wear suitable gloves.
46	If swallowed, seek medical advice immediately and show this container or label.
51	Use only in well-ventilated areas.

Hazardous ingredients for labeling

p-Mentha-1,8-dien

Special rules for supplemental label elements for certain mixtures

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

Keep away from sources of ignition - No smoking.

Other hazards

SECTION 3: Composition/ information on ingredients

Mixtures

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to 67/548/EEC
64-17-5	200-578-6	ethanol	ca. 15	F R11
67-63-0	200-661-7	propan-2-ol	ca. 10	F R11; Xi R36; R67
74-98-6	200-827-9	propane	ca. 12	F+ R12
75-28-5	200-857-2	isobutane	ca. 23	F+ R12
106-97-8	203-448-7	butane	ca. 33	F+ R12
5392-40-5	226-394-6	citral	ca. 0,25	Xi R38; R43
118-58-1	204-262-9	Benzyl salicylate [Benzyl 2- hydroxybenzoate]	ca. 0,36	Xi R43; N R51/53
2050-08-0	218-080-2	Pentylsalicylat	ca. 0,25	N R51/53
5989-27-5	227-813-5	p-Mentha-1,8-dien	ca. 1,7	R10; Xi R38; R43; N R50-53

SECTION 4: First aid measures

Description of first aid measures

General information

In case of allergic reactions, specially at respiratory tract, seek medical treatment immediately. In case of stronger and long effects, specially on skin and respiratory tract, medical treatment is necessary.

In case of inhalation

In the event of symptoms refer for medical treatment.

In case of skin contact Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

Most important symptoms and effects, both acute and delayed Physician's information / possible symptoms Allergic symptoms

Indication of any immediate medical attention and special treatment needed Treatment (Advice to doctor)

Treat symptoms.

SECTION 5: Firefighting measures

Extinguishing media Suitable extinguishing media Alcohol-resistant foam ABC powder Carbon dioxide Water spray jet

Extinguishing media which must not be used for safety reasons Full water jet

Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon monoxide (CO) Carbon dioxide (CO2)

Advice for firefighters Special protective equipment for fire-fighters Use breathing apparatus with independent air supply (isolated). Do not inhale explosion and/or combustion gases.

Additional information

Cool endangered containers with water spray jet. Shown danger refers to the contents of the cans standing under pressure. Above 50 °C danger of burst under emission of atmosphere capable of explosion. Bring out containers from fire area. Collect contaminated firefighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation. Keep people away and stay on the upwind side. Keep away sources of ignition.

Pay attention to extension of gas especially at ground (heavier than air) and in direction of the wind.

Environmental precautions

Collect contaminated water / firefighting water separately. Do not discharge into the drains/surface waters/groundwater.

Methods and material for containment and cleaning up Take up with absorbent material (e.g. general-purpose binder). Additional Information Vapour can be explosive in the mixture with air.

Reference to other sections

SECTION 7: Handling and storage

Precautions for safe handling

Advice on safe handling

No special measures necessary if used correctly.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking Emergency cooling must be provided for the eventuality of a fire in the vicinity. Vapours can form an explosive mixture with air. The vapours of product are heavier than air. Formation of explosive gas mixtures in air. Pay attention to general rules of internal fire prevention. Avoid effect of heat.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels Ventilate store-rooms thoroughly. Provide floor with bunding.

Further information on storage conditions

Keep locked up, out of reach of children Protect aerosols against fall over. Storage temperature between 0 ℃ to 30 ℃ (=32 ℉ to 86 ℉), maximum 50 ℃ (=122 ℉). Protect from heat/overheating.

Information on storage stability

maximum storage time: 3 years.

С

Storage group 2B

Fire class

Specific end use(s)

SECTION 8: Exposure controls/personal protection

Control parameters

biological limits (TRGS 903)

CAS No	Name	Parameter	BGW	Examination	Test date
67-63-0	propan-2-ol	Aceton	50 mg/l	B	b
67-63-0	propan-2-ol	Aceton	50 mg/l	U	b

Exposure controls

Respiratory protection

Breathing apparatus in the event of high concentrations. Short term: filter apparatus, filter A

Hand protection

Gloves (solvent-resistant)

General protective measures

Avoid contact with eyes and skin Do not inhale aerosols

Hygiene measures

At work do not eat, drink, smoke or take drugs.

SECTION 9: Physical and chemical properties

Information on basic pl Form aerosol can (data refer to contents).	-	nemical properties Colour colourless, clear		Odour aromatic	alcoholic
Important health, safety	and environ	mental informatio	n		
	Value	Temperature	at	Method	Remark
pH value in delivery state	not applicab	e			
Acid number	not applicabl	e			
Flash point	-60 ℃			DIN 51755	information concerns to propellant
Ignition temperature	365 ℃			DIN 51794	information concerns to propellant
Lower explosion limit	1,5 Vol-%			DIN 51649	information concerns to propellant

	Value	Temperature	at	Method	Remark
Upper explosion limit	8,5 Vol-%			DIN 51649	information concerns to propellant
Vapour pressure	2,7 bar	20 °C		inside pressure of the aerosol can	
Density	0,63 g/cm3	20 ℃		liquid	information concerns to liquid phase
Solubility in water					multimiscible

Other information

SECTION 10: Stability and reactivity

Reactivity Chemical stability Possibility of hazardous reactions Conditions to avoid danger of bursting above 50 °C Incompatible materials Hazardous decomposition products

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity/Irritability/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	5000 mg/kg	rat	OECD 401	Information concerns to main component.
LD50 acute dermal	10000 mg/kg	rabbit		
LC50 acute inhalation	> 1800 mg/l (4 h)	rat	OECD	
Irritability skin	low irritant effect - not necessary to label			
Irritability eye	low irritant - no labeling duty			

Experiences made from practice

Allergic reactions possible (analogy-reasons).

Has a degreasing effect on the skin.

Frequent persistent contact with the skin may cause skin irritation.

Additional information

No toxical dates available. Toxical dates refer to solvent. Labelling in compliance with the assessment procedure specified in the EC guidelines 1999/45/EC.

SECTION 12: Ecological information

Toxicity

Ecotoxicological effects

	Value	Species	Method	Validation
Fish	LC50 > 2000 mg/l (96 h)	Leuciscus idus	OECD 203, letha	ality
Daphnia	EC50 > 5000 mg/l (48 h)	Daphnia magna	OECD 202	
Algae	EC50 > 100 mg/l	Scenedesmus subspicatus	OECD 201	
Persistence	and degradability			
Biological degradabilit	у			Biodegradable
Bioaccumul	ative potential			
Mobility in s	oil			
Results of P	BT and vPvB assessment			
Other adver	se effects			
	ulation uncontrolled leakage of produ ion to ecology refers to solver			

SECTION 13: Disposal considerations

Waste treatment methods	
Waste code No.	Name of waste
20 01 40	metals

Recommendations for the product May be taken to household waste disposal or incineration plant, but care for official regulations.

Recommendations for packaging Totally emptied packaging may be taken for recycling.

SECTION 14: Transport information

Land and inland navigation transport ADR/RID UN 1950 AEROSOLS (butane), 2.1, (D), Classification code: 5F Marine transport IMDG UN 1950 AEROSOLS (butane), 2 Air transport ICAO/IATA-DGR UN 1950 Aerosols, flammable (butane), 2.1 Transport/further information Regulations concerning free quantities are to be observed.

Special precautions for user

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture Other regulations (EU) Aerosol directive (75/324/EEC).

Aerosol directive (75/324/EEC)

National regulations Water hazard class

Mixture-WGK

Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

3

SECTION 16: Other information

Wording of the R/H-phrases specified in chapter 3 (not the classification of the mixture!)

R 10 Flammable.

R 11 Highly flammable.

R 12 Extremely flammable.

R 36 Irritating to eyes.

R 38 Irritating to skin.

R 43 May cause sensitisation by skin contact.

R 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 67 Vapours may cause drowsiness and dizziness.